

Technical Datasheet

Date: 18.02.20

Page 1 of 2

EN ISO 13485 certified		
Article - No:	04-212-1203	Revision: 4
Remarks	piercable cap	single use only

Specification

Product	np Safelock-Cap microcentrifuge tube PP, 1,5ml, attached cap, boil-proof, yellow, grad., writing area, np pcr ready, max. RCF 30.000g, autocl. up to 121°C, CE/IVD
Classification	CE/IVD
Dimensions	outer diameter: 10,80 mm (+/- 0,2 mm)
	height (without cap): 38,90 mm (+/- 0,2 mm)
Colour	yellow
Graduation	grad., writ. area
Nominal Capacity	1,5ml
Material Characteristics	polypropylene (PP)
Temperature range	-70°C - 75°C
	in waterbath up to 120 °C
Autoclavability	autocl. up to 121°C
Centrifugation	max. RCF 30.000g
Product Characteristics	biologically inert
	physiologically harmless
	constantly usable at temperature of 80 °C up to 100 °C
Purity Grade	free of PCR inhibitors
	free of human DNA
	free of RNase and DNase
	free of pyrogens
Shelf - Life	not limited at controlled storage conditions
Packaging	pcs per bag: 1.000
	pcs per carton: 8.000
	pcs per pallet: 160.000
Storage	dry condition: 40%-60% rel. humidity
	bags / cases orig. closed
	storage temp. +2°C to max. +30°C

Technical Datasheet

Date: 18.02.20

Page 2 of 2

	pal. not stackable
Approved by nerbe plus quality department	